

## 1. IDENTIFICATION

**Product Name:** CorrosionX<sup>®</sup> Aviation  
**Product Numbers:** 80103, 84004, 84005, 84002, 84001  
**Product Type and Use:** Corrosion Inhibitor / Moisture Displacer / Lubricant  
**Manufacturer:** Corrosion Technologies  
2850 Industrial Ln, Garland, TX 75041  
**Contact:** Telephone: 972-271-7361 Fax: 972-278-9721  
**Emergency Telephone:** CHEMTREC<sup>®</sup> USA (800) 424-9300  
Outside US +1 (703) 527-3887

## 2. HAZARDS IDENTIFICATION

### Hazard Classification

**Health Hazard(s)**  
Eye Irritation Category 2B

**Physical Hazard(s)**  
None

**Hazard(s) not otherwise classified**  
None

### Labeling

**Signal Word:** WARNING  
**Pictograms:** Exclamation Mark



### Statements of Hazard

#### Hazard Statements

Causes eye irritation

#### Precautionary Statements

Wear protective gloves. Wash thoroughly after handling. Wash contaminated clothing before reused. Dispose of contents and container in accordance with applicable regulations.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical attention.

If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs; get medical attention.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>90*

\* Exact percentage of composition has been withheld as a trade secret

## 4. FIRST AID MEASURES

**General Advice:** Causes eye irritation. Avoid eye contact. May cause skin sensitization. Avoid skin contact. Do not swallow. Use with adequate ventilation. Avoid breathing mist.

**Inhalation:** Remove from exposure area to fresh air. Give artificial respiration if not breathing. Get medical attention.

**Skin Contact:** Wipe excess from skin; remove contaminated clothing and wash before reuse. Wash with soap and water.

**Eye Contact:** Flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison control center.

## 5. FIRE FIGHTING MEASURES

**Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Suitable:** Carbon Dioxide, Dry Chemical, and Foam

**Unsuitable:** Alcohol, Alcohol based solutions, any other media not listed above.

**Fire Fighting Procedures:** As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Unusual Fire and Explosion Hazards:** None known.

**Hazardous Combustion/ Decomposition Products:** Oxides of carbon, sulfur, calcium, magnesium and phosphorous.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions / Protective Equipment / Emergency Procedures:** Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment.

**Methods and materials for containment and cleaning up:** Do not flush into surface water or sanitary sewer system. Dike and contain spillage. Soak up with absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Use clean tools to collect absorbed material and transfer to a properly labeled container for disposal according to applicable regulations.

## 7. HANDLING AND STORAGE

### HANDLING

**Precautions for Safe Handling:** Avoid eye contact. Use with adequate ventilation. Avoid breathing mist. Follow all SDS/label precautions even after container is empty due to residue.

### STORAGE

**Conditions to avoid:** Store in a cool, dry, well-ventilated place in the original container. Keep container closed when not in use. Avoid excess heating and high temperatures.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMITS

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Component	ACGIH		OSHA		STEL ppm	STEL mg/m <sup>3</sup>
	TLV ppm	TLV mg/m <sup>3</sup>	PEL ppm	PEL mg/m <sup>3</sup>		
Distillates (petroleum), hydrotreated heavy paraffinic	Not Est.	5	10	5	Not Est.	2500

**Engineering Controls:** Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

### Personal Protection

**Respiratory Protection:** None required under normal use conditions. In case of insufficient ventilation and for exposures above occupational exposure limits wear a NIOSH approved air purifying respirator with organic vapor cartridge.

**Hand / Skin Protection:** Wear impermeable gloves such as neoprene or nitrile rubber gloves. Gauntlets and apron may be worn depending on the extent and duration of exposure.

**Eye / Face Protection:** Safety glasses with side-shields. An eyewash station should be available to the area of use.

**General Hygiene Measures:** Avoid skin and eye contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Transparent	<b>Autoignition Temperature:</b>	Not established
<b>Physical State:</b>	Non-viscous liquid	<b>Volatile by volume (%):</b>	4
<b>Odor:</b>	Fresh scent	<b>Vapor Density (Air=1):</b>	5.9
<b>Color:</b>	Greenish-brown	<b>Evaporation Rate (BuAc=1):</b>	<1
<b>Viscosity, cSt @ 40°C:</b>	33.2	<b>Vapor Pressure, mmHg @20°C:</b>	<0.05
<b>cSt @ 100°C:</b>	7.0	<b>Solubility in water:</b>	Insoluble
<b>pH:</b>	Not applicable	<b>Octanol/Water Partition:</b>	Not established
<b>Boiling Point/ Range:</b>	>421°F / 216°C	<b>VOC Content g/l (%):</b>	0 (0)
<b>Melting Point:</b>	Not established	<b>Specific Gravity @15.6°C:</b>	0.895
<b>Flash Point:</b>	143°C / 290°F	<b>Pour Point:</b>	-22°F / -30°C
<b>Method:</b>	Cleveland Open Cup	<b>Non-volatile by Volume (%):</b>	96
<b>Lower Explosive Limit, vol %:</b>	Not Est.	<b>Dielectric Strength (KV):</b>	30
<b>Upper Explosive Limit, vol %:</b>	Not Est.		

## 10. STABILITY AND REACTIVITY

**Stability:** Stable at ambient temperatures.

**Conditions to Avoid:** Excess heating above 356°F / 180°C over long periods of time degrades the resin. Avoid high temperatures.

**Hazardous Polymerization:** Will not occur by itself, but masses of more than one pound of product plus an aliphatic amine will cause irreversible polymerization with considerable heat.

**Materials to Avoid:** Bases, acids, amines and oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

**Product Information:** Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in severe injury to the lungs and death.

### Ingredient Information

Distillates (petroleum), hydrotreated heavy paraffinic: OrL-rat LD50 >5000 mg/kg, Skn-Rbt LD50 - 2,000 mg/kg, Ihl-rat LC50: >2,000 mg/kg

Alkenyl Amine: May cause sensitization by skin contact (supplier information)

### Acute Effects

**Signs and Symptoms of Overexposure:** Allergic skin reaction, Eye irritation, Coughing, Sneezing

**Inhalation:** May cause coughing and sneezing.

**Skin Contact:** May cause allergic skin reaction. May be slightly irritating to sensitive users. Prolonged and repeated contact with skin without adequate cleaning may clog the pores of the skin and may result in disorders such as oil acne (folliculitis) in sensitive individuals.

**Eye Contact:** May cause stinging, tearing and redness.

**Ingestion:** May cause nausea, vomiting and diarrhea. Ingestion and subsequent vomiting may result in aspiration of the product into the lungs resulting in chemical pneumonitis, pneumonia and pulmonary edema.

**Primary Route(s) of Exposure:** Skin, Eyes, Inhalation

**Primary Route(s) of Entry:** Skin, Inhalation, Ingestion

**Target Organs:** Skin, Eyes, Lungs

**Chronic Effects:** May cause skin sensitization

**Carcinogenicity:** Highly refined base oil blend (< 3 % DMSO extractable) ACGIH group A4; not classified as human carcinogen.

**Medical Conditions Aggravated by Exposure:** May aggravate existing skin, eye and respiratory conditions such as asthma and dermatitis.

## 12. ECOLOGICAL INFORMATION

### Product Data

**Toxicity to Fish:** Not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water.

**Toxicity to Terrestrial Plants:** If applied to leaves, may kill grasses and small plants by interfering with transpiration and respiration.

**Toxicity to Above-Ground Organisms:** May be moderately toxic to amphibians by preventing dermal respiration. May cause gastrointestinal distress in birds and mammals through ingestion.

**Ingredient Data:** Not established

**Elimination Information:** Expected to be not readily biodegradable. The major oil component is expected to biodegrade over period of 100-120 days in aerobic environment at temperature above 70°F (21°C), however finished product contains components that may persist in the environment. Contains constituents with the potential to bioaccumulate in aquatic organisms.

### 13. DISPOSAL CONSIDERATIONS

**Product:** Dispose of in accordance with applicable regulations.

**Container:** Empty remaining contents. Empty containers should be taken for local recycling, recovery or waste disposal. Empty containers may contain residues. Do not cut, weld or grind empty containers.

### 14. TRANSPORT INFORMATION

**Road Transport**

DOT Hazard Class: Not Regulated

**Sea Transport**

IMDG/GGV See Class: Not Regulated

**Air Transport**

ICAO/IATA Class: Not Regulated

### 15. REGULATORY INFORMATION

**U.S. Federal Regulations**

**Toxic Substances Control Act (TSCA):** All components are included on the Inventory

**Superfund Amendments and Reauthorization Act (SARA) Title III:**

Immediate Hazard	Delayed Hazard	Fire Hazard	Pressure Hazard	Reactivity Hazard
Yes	No	No	No	No

### 16. OTHER INFORMATION

**Prepared by:** Corrosion Technologies, Technical Services Department

**Revision Date:** 4/24/2023

**Supersedes Date:** 6/24/2020

**Revision Indicator:** v 4.0

National Fire Protection Association (704)

Health: 1      Flammability: 1      Reactivity: 0      Other:

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.